





Dimension Unit : mm



Software

- 4MP (2592×1520)
- 2D / 3D DNR
- Support smart phone, iPad, remote monitoring
- ROI
- Video exception, line crossing, intrusion, etc.

Hardware Specification

- 1 / 3 "CMOS
- Built-in IR Cut Removable.
- Aluminum Alloy Housing for Better Heat Dissipation.
- Built-in PoE.
- Class IP66 Weatherproof.
- 30M IR distance.

Specifications

Model	HS-T039RV
Image Sensor	1 / 3 "CMOS
Image Size	2592 × 1520
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Min. Illumination	0.02 lux @F1.2, AGC ON; 0 lux with IR
Lens	3.6 mm @F1.6, horizontal field of view: 85° (2.8 mm, 6 mm optional)
Day & Night	ICR
Wide Dynamic Range	120 dB
Digital NR	2D / 3D DNR
Video Compression	H.265 MP; H.264 MJPEG
Resolution	4MP (2592×1520), 2K (2560×1440), 3MP (2304×1296), 3MP (2048×1536), 1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
Main Stream	60Hz : 4MP(1~20fps)/2K(1~20fps)/3MP(1~30fps)/1080P(1~30fps)/720P(1~30fps) 50Hz : 4MP(1~20fps)/2K(1~20fps)/3MP(1~25fps)/1080P(1~25fps)/720P(1~25fps)
Bit Rate	128 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Network	Ethernet (10/100Base-T), RJ45 connector
Remote Monitoring	IE browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Storage	Network remote storage
Smart Alarm	Motion alarm
Smart Analysis	Video exception, line crossing, intrusion, etc.
PoE	Yes
IR Distance	30 m
Ingress Protection	IP66
Power Supply	DC12V / PoE
Power Consumption	< 2.5W
Operating Environment	- 20 °C ~ 50 °C, 10 % ~ 90 % relative humidity
Dimensions (mm)	Φ87 × 219
Weight (net)	595g